


Pannello Led 60x60

Pannello Led - Led panel



Apparecchi

IT

- Plafoniera LED per controsoffittatura a pannelli 60x60
- Cornice in alluminio, lastra frontale in plexiglass opale
- Basso decadimento del flusso dei Led
- Lunga durata
- Utilizza chip Led di alta qualità e ad altissima efficienza
- Luce brillante
- Non nuoce agli occhi
- 100% assenza di strobo flash
- Adatta per appartamenti, ospedali, hotel, uffici
- Alimentatore a corrente costante incluso
- Versioni 30x30, 30x60, 60x120
- CRI>80
- Ta -10 ÷ +45°C
- Alimentatori regolabili 1-10, DALI, CONEX, Push disponibili a richiesta

EN

- Led fixture used for 60x60 false ceiling
- Aluminium edge, opal plexiglass frontal panel
- Very low flux decline
- High efficiency led chip used
- Bright light
- Does not harm the eyes
- 100% absence of strobo flash
- Can be used for apartment, hospital, hotels, office
- Led constant driver included
- Available on request: 30x30, 30x60, 60x120
- CRI>80
- Ta -10 ÷ +45°C
- 1-10V, DALI, CONEX, Push, dimmable power supply available on request



(W)	(LM)	(V)	mA	(K)	Led Type	Size (mm) AxBxC	(KG)	PF	
30	3000	220-240V AC	1200	3000	162x2835	596x596x12	2.8	>0,9	
30	3100	220-240V AC	1200	4000	162x2835	596x596x12	2.8	>0,9	
35	3500	220-240V AC	900	4000	180x2835	596x596x12	2.8	>0,9	UGR<19
36	3100	220-240V AC	1200	6000	162x2835	596x596x12	2.8	>0,9	
45	4100	220-240V AC	1500	4000	198x2835	596x596x12	2.8	>0,9	
45	4136	220-240V AC	1500	6000	198x2835	596x596x12	2.8	>0,9	
36	3100	220-240V AC	1200	4000	162x2835	596x596x12	2.8	>0,9	
36	3100	220-240V AC	1200	6000	162x2835	596x596x12	2.8	>0,9	

